



# GuestCall

## COASTER PAGERS

### **Instant customer notification for order collection.**

Allows kitchen to instantly notify guests when their meals are ready. Perfect for noisy environments in pub bistros, bars, beer gardens, casual dining restaurants and take away businesses.

Kitchen can instantly notify guests when their meals are ready increasing efficiency for order pick up at dine-ins or take-aways.

### **Pager Features**

- 3 km range, unique ID to prevent interference
- Durable for high volume use
- Rechargeable or replaceable batteries 2 – 3 year battery life (use dependent)
- Smart alerts – out of range and pager search
- Space saving stackable charging solution
- On pager advertising options
- Flash, beep and vibration notifications

### **Transmitter Features**

- Auto pager renumbering technology
- Supports up to 9999 pagers including guest and staff pagers
- 3 km range, unique ID to prevent interference
- Smart alerts – out of range and pager search
- Space saving stackable charging solution

Designed and manufactured by JTech (HME), the pioneer in wireless paging technology with 25 years of experience.

## Industries



CASUAL  
DINE-IN



TAKE-AWAY



PUB BARS



BISTROS



BEER  
GARDENS

sales@gravityaustralia.com.au  
1300 832 876  
U5, 63-71 Boundary Rd,  
North Melbourne, Victoria 3051, Australia

### COASTER PAGER TECHNICAL SPECIFICATIONS

Coaster Pager Dimensions	Diameter	Height	Weight
	10.8 cm	2.1 cm	0.17 kg
Pager Label Dimensions	6.98 cm diameter round		
Rechargeable Battery	Nickel Metal Hydride (NiMH)		
	Indicator light while charging or when needs replacement 2-3 year pager battery life (dependent on use)		
Long Range Technology	UHF Frequency		
	Unique System ID eliminates interference Exceptional site coverage		

### CHARGING BASE TECHNICAL SPECIFICATIONS

Charger Dimensions	Diameter	Height	Weight
	10.8 cm	2.1 cm	0.17 kg
Smart Charging	Space-saving stack charger		
	Charges all pagers in 2 hours Extends battery life without overcharging		

### IQ TRANSMITTER TECHNICAL SPECIFICATIONS

Transmitter Dimensions	Width	22 cm
	Depth	14 cm
	Height	6 cm
	Weight	0.72 kg
Display	7.6 x 5 cm	
	8 line text display	
	Blue LED back lit digital screen	
	Water-resistant polyurethane	
Interfaces	Serial: DB9-DCE (female) Connector	
	Data Rates: 1200, 9600, 38400, 57600	
	Characters: 8 Data Bits	
	Stop Bits: 1	
Electrical	Frequency range: 450 - 468 MHZ	
	FCC Identifier: WDC-IQBASE-N	
	Channel Spacing: 12.5KHz	IC Identifier: 7752A-IQBASE-N
	Speed / Baud Rate: 512/1200 bps	
Power	DC 12V, 3.5A, SMPS	
	RF Output: 2 Watts	
	Format: POCSAG	
Long Range Technology	UHF Frequency	
	Unique System ID eliminates interference Up to 3 km of site coverage	