



BIOPTIC SCANNER SCALE

This bi-optic scanner is the highest performance 5-sided POS scanner available today.

It improves operational efficiency by achieving outstanding first-pass read rates, and represents the next step in value and checkout productivity.

- Aggressive and ergonomic design
- Accurate produce and bulk food weighing
- Multiple interface solution
- Flash memory for easy software upgrades

IN-COUNTER SCANNER SCALE

DECODING CAPABILITY

1D / Linear Codes	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes
Stacked Codes	GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional

ELECTRICAL

Ac Power Requirements	AC Input: 100-250 VAC, 50-60 Hz		
Power Consumption	Operating (Maximum)	Operating (Nominal)	Sleep Mode
	8 Watts	7 Watts	4 Watts
ENVIRONMENTAL	Minimum		Maximum

Esd Protection	25 kV (Air discharge) 64mm (including backing paper)
Humidity	5 - 95% (Non-condensing) 200mm
Temperature	Operating: 10 to 40 °C / 50 to 104 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F

INTERFACES

Interfaces	IBM 46xx; Keyboard Wedge: Scanner Only; OEM (IBM) USB; RS-232; USB: Scanner Only
Auxiliary Ports	EAS Port: Powered RS-232; Remote Scale Display; Scale Host

READING PERFORMANCE

Motor Speed	6,000 rpm
Read Height	15.2 cm / 6.0 in
Read Rate (Maximum)	5,200 lines/sec
Reading Indicators	Beeper (Adjustable Tone and Volume); Good Read LED
Scan Lines	52
Scan Zone	360°
Sides Read	5 Sides

SAFETY & REGULATORY

Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications.
Environ. Compliance	Complies to EU RoHS
Laser Classification	Caution Laser Radiation - Do not stare into beam; CDRH Class IIa; EN 60825 Class 1; IEC 60825 Class 1

PHYSICAL

Dimensions	Depth (Below Counter)	Height (Above Counter)	(Medium) Length		
	10.2 cm / 4.0 in	13.0 cm / 5.1 in	40.1 cm / 15.8 in		
Scale Capacities	Adjustments Required	Capacity	Maximum Static Weight	Minimum Increment	Vibration Immunity
	Calibration Only	15.0 kg / 30.0 lb	68.0 kg / 150.0 lb	0.005 kg / 0.010 lb	4 Programmable Filter Settings

OPTIONAL FEATURES

All-Weights Scale Platter	Integrated Produce Lift Bar; Produce Rail™
Eas Features	Checkpoint Systems: Integrated EAS hardware will work with Counterpoint IX and Evolve D11 models; Sensormatic: Good Read Acknowledgement
Value Added Featuresplatter	Cashier Training™; Diagnostic Reporting; Host Download; Productivity Index Reporting™ (PIR)

WARRANTY	1-YEAR FACTORY WARRANTY
----------	-------------------------

sales@gravityaustralia.com.au
 1300 832 876
 U5, 63-71 Boundary Rd, North Melbourne, Victoria 3051, Australia